

# WHD8001B



## IPTV/OTT Box



## INTRODUCTION

WHD8001B is a high performance Android STB that can support up to 4K video decoding. With Android 9.0 Operation System, it can support both our own IPTV APK and any other third-party APK. With Mpeg-2/H.264/H.264 video decoding and all mainstream audio decoding capability, it can be widely used in different IPTV/OTT applications for HDMI/AV output with either Wifi or Ethernet network access.

## SPECIFICATIONS

System Information	
Chipset	Amlogic S905X
OS	AOSP 9.0
CPU	Quad core ARM CortexA53 1.5GHz
GPU	Mali450
Memory	1GB
FLASH	8GB
Video Picture decode	<ul style="list-style-type: none"><li>• VP9 Profile-2 up to 4Kx2K@60fps</li><li>• H.265 HEVC MP-10@L5.1 up to 4Kx2K@60fps</li><li>• H.264 AVC HP@L5.1 up to 4Kx2K@30fps</li><li>• H.264 MVC up to 1080P @60fps</li><li>• MPEG-4 ASP@L5 up to 1080P@60fps (ISO-14496)</li><li>• WMV/VC-1 SP/MP/AP up to 1080P@60fps</li><li>• AVS-P16 (AVS+) /AVS-P2 JiZhun Profile up to 1080P@60fps</li><li>• MPEG-2 MP/HL up to 1080P@60fps (ISO-13818)</li><li>• MPEG-1 MP/HL up to 1080P@60fps (ISO-11172)</li><li>• RealVideo 8/9/10 up to 1080P@60fps</li><li>• WebM up to VGA</li><li>• Multiple language and multiple format sub-title video support</li><li>• MJPEG and JPEG unlimited pixel resolution decoding (ISO/IEC-10918)</li><li>• Supports JPEG thumbnail, scaling, rotation and transition effects</li><li>• Supports *.mkv,*.wmv,*.mpg,*.mpeg,*.dat,*.avi,*.mov,*.iso,*.mp4,*.rm and *.jpg file formats</li></ul>
Audio decode	<ul style="list-style-type: none"><li>• Supports MP3, WMA, RM, FLAC, Ogg, DTS Optional and programmable with 7.1/5.1 down-mixing</li><li>• I2S audio interface supporting 2-channel input and 8-channel (7.1)</li><li>• Built-in serial digital audio SPDIF/IEC958 output and PCM input/output</li><li>• Built-in stereo audio DAC</li><li>• Stereo digital microphone PDM input</li><li>• Supports concurrent dual audio stereo channel output with combination of analog+PCM or I2S +PCM</li></ul>

Peripheral Interface	
USB	2xUSB2.0
Video/Audio Output	1xHDMI2.0 + 1xAV
Network	1xRJ45 (10/100Mbps)
WIFI	2.4GHz+5GHz
BLT	V4.2
Power Interface	1xDC 12V/1A
Power Switch	1xPower on/off
LED	Power/Standby + Network Status + IR Status
Other Information	
Remoter	BLT or IR
Dimensions	110x110x26mm
Operating Temperature	-5°C~55°C
Storage Temperature	-20°C ~ 60°C
Working Humidity	20%~90%

\* The terms HDMI and HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing LLC in the United States and other countries.