

Passive Wall-Mount Speakers

▶ (SPK-AW4-10 / SPK-AW6-10 / SPK-AW4-10W / SPK-AW4-20)



This wall-mounted speaker works perfectly in various indoor settings.



KEY FEATURES

- Ensures easy integration with existing PA systems via 70V/100V rated voltage, enabling plug-and-play installation without extra adapters.
- Delivers lasting clarity and durability through speaker surround damping, reducing wear for stable sound in frequent use.
- Offers 10W/20W power options to flexibly suit various space sizes, ensuring optimal audio for both small rooms and large areas.

TECHNICAL SPECIFICATIONS

Model	SPK-AW4-10	SPK-AW6-10	SPK-AW4-10W	SPK-AW4-20
Rated Power	10 W	6-10 W	5/10W	20 W
Rated Voltage	70 V / 100 V			
Speaker Driver	1× 6.5", 1× 2"	1× 6.5"	1× 4.5"	1× 4", 1× 1"
Sensitivity (1m, 1W)	92(±2) dB	92(±2) dB	87(±2) dB	89(±2) dB
Sound Pressure Level (SPL) (1m)	100(±2) dB	100(±2) dB	97(±2) dB	102(±2) dB
Frequency Response	160 Hz-18 kHz	160 Hz-18 kHz	80 Hz-18 kHz	80 Hz-18 kHz
Dimension (W×H×D)	273×183×115 mm	270×110×200 mm	270×210×115 mm	160×150×225 mm
Weight	1.75 kg	0.9 kg	2.0 kg	2.8 kg

ORDERING INFORMATION

Model	Description		
SPK-AW4-10	Gray, 10W, outdoor column speaker with 70V/100V rated voltage input		
SPK-AW6-10	Gray, 20W, outdoor column speaker with 70V/100V rated voltage input		
SPK-AW4-10W	Black, 30W, outdoor column speaker with 70V/100V rated voltage input		
SPK-AW6-20	Black, 40W, outdoor column speaker with 70V/100V rated voltage input		

DIMENSION DRAWING



SPK-AW4-10



SPK-AW4-10W



SPK-AW6-10



SPK-AW6-20